


# LAC 640



**867** (RAL 9010)  
1.50 - 2.50 - 3.00 m  
x 60-250 ml




**810** (RAL 9005)  
1.50 m x 60 ml  
3.00 - 3.20 m  
x 60-250 ml



**640 g/m<sup>2</sup>**



**3m**



**7462**  
3.00 m x 60-250 ml



**7350**  
3.00 m x 60-250 ml



**7458** (RAL 1015)  
3.00 m x 60-250 ml



**7441** (RAL 1021)  
3.00 m x 60-250 ml



**7445** (RAL 2008)  
3.00 m x 60-250 ml



**7444** (RAL 2004)  
3.00 m x 60 ml



**7446** (RAL 3002)  
1.50 - 3.00 m  
x 60-250 ml




**7450** (RAL 5015)  
1.50 - 3.00 m  
x 60-250 ml




**941**  
1.50 m x 60 ml  
2.50 - 3.00 - 3.20 m  
x 60-250 ml



**995** (RAL 6026)  
1.50 m x 60 ml  
2.50 - 3.00 - 3.20 m  
x 60-250 ml



**7345** (RAL 6014)  
3.00 m x 60-250 ml



**939**  
1.50 m x 60 ml  
2.50 - 3.00 - 3.20 m  
x 60-250 ml




**7196** (RAL 7037)  
1.50 m x 60 ml  
2.50 - 3.00 - 3.20 m  
x 60-250 ml



**7301** (RAL 9006)  
3.00 m x 60-250 ml



**7412** (RAL 7024)  
3.00 m x 60-250 ml



**7705** (RAL 7016)  
3.00 m x 60 ml

# ECOLAC 640



**7196** (RAL 7037)  
3.00 m x 60-250 ml

Limited availability. Reverse side colour may vary.

 *Disponibilité limitée. Coloris face envers non constant.*

 *Begrenzte Verfügbarkeit. Farbabweichungen auf der Rückseite, bei Restpastenwaren, sind produktionsbedingt.*

 *Disponibilidad limitada. El color en la cara interna puede variar.*

 *Disponibilità limitata. Il colore del rovescio può variare.*



	<b>LAC 900</b>	<b>DICOPLAN</b>	<b>LAC 680</b>	<b>LAC 640</b>	<b>UNILAC</b>
<b>Base cloth</b> <i>Support / Trägergewebe</i> <i>Soporte / Supporto</i>	1100 dtex PES HT	1100 dtex PES HT	1100 dtex PES HT	1100 dtex PES HT	1100 dtex PES HT
<b>Coating</b> <i>Enduction / Beschichtung</i> <i>Revestimiento / Spalmatura</i>	PVC (Lowick)	PVC (Lowick)	PVC (Lowick)	PVC (Lowick)	PVC (Lowick)
<b>Finish</b> <i>Finition / Ausrüstung</i> <i>Acabado / Finizione</i>	Cleangard	Cleangard	Cleangard	Cleangard	Cleangard
<b>Total weight</b> <i>Poids Total / Gesamtgewicht</i> <i>Peso total / Peso totale</i>	900 g/m <sup>2</sup>	680 g/m <sup>2</sup>	680 g/m <sup>2</sup>	640 g/m <sup>2</sup>	540 g/m <sup>2</sup>
<b>Tensile strength</b> > NF EN ISO 1421 <i>Résistance rupture / Reissfestigkeit</i> <i>Resistencia a la rotura</i> <i>Resistenza alla rottura</i>	400/400 daN / 5 cm	260/250 daN / 5 cm	220/210 daN / 5 cm	220/210 daN / 5 cm	220/210 daN / 5 cm
<b>Tear strength</b> > DIN 53363 <i>Résistance déchirure</i> <i>Weiterreissfestigkeit</i> <i>Resistencia al desgarrar</i> <i>Resistenza allo strappo</i>	60/50 daN	32/28 daN	30/25 daN	30/25 daN	25/20 daN
<b>Adhesion</b> > NF EN ISO 2411 <i>Adhérence / Haftung</i> <i>Adherencia / Aderenza</i>	10 daN / 5 cm	10 daN / 5 cm	8 daN / 5 cm	8 daN / 5 cm	8 daN / 5 cm
<b>Temperature resistance</b> > NF EN 1876-2 <i>Températures d'utilisation</i> <i>Temperaturbeständigkeit</i> <i>Resistencia máxima a la temperatura</i> <i>Resistenza alla temperatura</i>	-30°C +70°C (24h)	-30°C +70°C (24h)	-30°C +70°C (24h)	-30°C +70°C (24h)	-30°C +70°C (24h)
<b>Flame Retardancy</b> > DIN 75200 <i>Ignifugation / Brennverhalten</i> <i>Ignifugación / Ignifugazione</i>	< 100 mm/min	< 100 mm/min	< 100 mm/min	< 100 mm/min	< 100 mm/min



Saint Clair Textiles PVC fabrics are recyclable

 *Les produits PVC Saint Clair Textiles sont recyclables*

 *Alle PVC-beschichteten Saint Clair Textiles Produkte sind recyclebar*

 *Todos los artículos recubiertos de PVC Saint Clair Textiles son reciclables*

 *Tutti i prodotti in PVC Saint Clair Textiles sono riciclabili*




All PVC coated fabrics can be slit

 *Tous les articles enduits PVC sont tronçonnables*

 *Für alle PVC-beschichteten Produkte gibt es den Schneide-Service*


 *Todos los artículos recubiertos de PVC se pueden cortar*

 *Tutti i prodotti spalmati in PVC si possono tagliare nella misura desiderata*




Other colours are available on special production

 *Autres coloris possibles sur fabrications spéciales*

 *Andere Farbe mit Sonderproduktion möglich*









 *Otros colores disponibles bajo pedido mínimo*

 *É possibile realizzare colori diversi per produzioni speciali*

*Average values, non-contractual*

*Valeurs moyennes, non-contractuelles / Alle angegebenen Werte sind ca. Werte / Valores medios y no contractuales / Questi valori medi non hanno valore contrattuale*

		 900 g/m²		 680 g/m²		 640 g/m²		 540 g/m²	
		 LAC 900		 DICOPLAN		 LAC 640		 UNILAC	
REF.	RAL	M	ML	M	ML	M	ML	M	ML
867	9010	3,00 3,20	30-60-200 60-200	2,50-3,00	30-60-250	1,50 2,50-3,00	60 60-250	3,00	60-250
7455	9016	3,00	30-60-200	2,50	30-60-250	-	-	-	-
7457	1013	-	-	2,50	30-60	-	-	-	-
7458	1015	3,00	30-60-200	2,50	30-60-250	3,00	60-250	-	-
7462	-	-	-	-	-	3,00	60-250	-	-
7350	-	-	-	-	-	3,00	60-250	-	-
7443	1014	3,00	30-60-200	2,50	30-60-250	-	-	-	-
7440	1018	3,00	30-60-200	2,50	30-60-250	-	-	-	-
7441	1021	3,00	30-60-200	2,50-3,00	30-60	3,00	60-250	-	-
7456	1003	3,00	30-60-200	2,50-3,00	30-60	-	-	-	-
7445	2008	3,00	30-60-200	2,50	30-60	3,00	60-250	-	-
7444	2004	3,00	30-60-200	2,50	30-60	3,00	60	-	-
7447	3020	3,00	30-60-200	2,50	30-60-250	-	-	-	-
7523	-	3,00	30-60-200	-	-	-	-	-	-
7446	3002	3,00	30-60-200	2,50-3,00	30-60-250	1,50 3,00	60 60-250	-	-
887	8017	-	-	2,50	30-60-250	-	-	-	-
7449	5012	3,00	30-60-200	2,50	30-60-250	-	-	-	-
7450	5015	3,00	30-60-200	2,50	30-60-250	1,50 3,00	60 60-250	-	-
7307	5010	3,00	30-60-200	2,50	30-60-250	-	-	-	-
941	-	3,00	30-60-200	1,50 2,50-3,00	60 30-60-250	1,50 2,50-3,00-3,20	60 60-250	3,00	60-250

		 900 g/m²		 680 g/m²		 640 g/m²		 540 g/m²	
		 LAC 900		 DICOPLAN		 LAC 640		 UNILAC	
REF.	RAL	M	ML	M	ML	M	ML	M	ML
7290	5002	3,00 3,20	30-60-200	2,50	30-60-250	-	-	-	-
7448	5003	3,00	30-60-200	2,50	30-60-250	-	-	-	-
7309	5013	3,00	30-60-200	2,50	30-60-250	-	-	-	-
7451	6005	3,00	30-60-200	2,50	30-60	-	-	-	-
7454	6028	3,00	30-60-200	-	-	-	-	-	-
7491	-	3,00	30-60-200	-	-	-	-	-	-
995	6026	3,00	30-60-200	2,50-3,00	30-60-250	1,50 2,50-3,00-3,20	60 60-250	3,00	60-250
7452	6018	3,00	30-60-200	3,00	30-60-250	-	-	-	-
7345	-	-	-	-	-	3,00	60-250	-	-
7459	7035	3,00	30-60-200	2,50	30-60-250	-	-	-	-
7374	7038	3,00	30-60-200	2,50	30-60-250	-	-	-	-
7344	-	-	-	2,50	30-60	-	-	-	-
939	-	3,00	30-60-200	2,50-3,00	30-60-250	1,50 2,50-3,00-3,20	60 60-250	3,00	60-250
7301	9006	3,00	30-60-200	2,50-3,00	30-60	3,00	60-250	-	-
7196	7037	3,00	30-60-200	2,50	30-60-250	1,50 2,50-3,00-3,20	60 60-250	-	-
7412	-	-	-	-	-	3,00	60-250	-	-
7705	7016	-	-	-	-	3,00	60-250	-	-
810	9005	3,00	30-60-200	2,50	30-60-250	1,50 3,00-3,20	60 60-250	-	-

Saint Clair Textiles unique anti-wicking process helps the fabric to last longer and look like new.

**[FR]** Traitement spécifique à Saint Clair Textiles pour empêcher la moisissure par capillarité. Le tissu dure plus longtemps et garde son aspect d'origine.

**[DE]** Das einzigartige Herstellungsverfahren von Saint Clair Textiles verhindert Schimmelbildung. Das Gewebe hat eine längere Lebensdauer und behält seine ursprüngliche Optik.

**[ES]** Tratamiento específico de Saint Clair Textiles para evitar el moho por capilaridad, ayuda al tejido a durar más tiempo y se vea como nuevo.

**[IT]** Trattamento specifico Saint Clair Textiles per impedire la muffa per capillarità. Il tessuto aumenta la sua durata nel tempo mantenendo il suo aspetto originale.

## FINITION CLEANGARD

The smooth Cleangard topcoat lacquer prevents soiling and facilitates cleaning. A solid protection against weathering.

**[FR]** Traitement sur les deux faces pour un état de surface lisse et moins salissant. Une protection résistante aux intempéries.


**[DE]** Oberflächenbehandlung auf beiden Seiten für eine glatte und stärker schmutzabweisende Oberfläche.

Wirksamer Schutz gegen Witterungseinflüsse.

**[ES]** Tratamiento en las dos caras para conseguir una superficie lisa y más limpia. Una protección resistente a la intemperie.

**[IT]** Trattamento sulle due facce per garantire una superficie liscia e meno sensibile allo sporco. Una protezione resistente alle intemperie.

### Classic coatings



#### Moisture penetration


Enduction classique : pénétration de l'humidité

Klassisches Beschichtungsverfahren : feuchtigkeitsdurchdringung

Recubrimiento clásico : penetración de humedad

Spalmatura classica : penetrazione dell'umidità

### Saint Clair Textiles LOWICK System



#### Total coating impregnation of the yarn

Imprégnation totale des fils dans la matière

Vollständige Imprägnierung des Garns im Gewebe

Impregnación total del hilo del material

Impregnazione totale dei fili nel materiale

## ADVANTAGES

### Avantages / Vorteile / Ventajas / Ventaggi



#### All-weather resistant

Résistant aux intempéries /

Wetterbeständig /

Resistente a la intemperie / Re-

sistente alle intemperie



#### Easier to clean

Plus facilement nettoyable /

Leichter zu reinigen /

Más fácil de limpiar /

Più facile da pulire



#### Very good weldability

Trés bonne soudabilité /

Sehr gute Schweißbarkeit /

Muy buena soldabilidad /

Ottima saldabilità



#### Longer life

Plus de longévité / Längere

Lebensdauer / Mayor vida útil /

Maggiore durata



#### Suppleness

Souple / Flexibilität / Flexibilidad /

Buona flessibilità



#### Smoother surface, less prone to soiling.

Plus lisse et moins adhérente aux salissures /

Glatter und weniger schmutz-anfällig /

Más lisa y menos adherente para las manchas /

Più liscia e meno sensibile allo sporco.