

**Stamskin** Zen

A unique response to achieve total hygiene



## Stamskin Zen

### Applications

Indoor furniture ensuring hygiene and comfort in demanding environments:

seats, medical and paramedical tables, wellness care, early childhood and public areas.



#### Non-cytotoxic and non-irritant

Stamskin Zen offers antimicrobial and antiviral properties without irritating users'skin. The formula is entirely phthalate free.

#### Bactericidal and virucidal

For optimal hygiene in the most demanding environments. Eliminates 99.9% of all bacteria\* and 99.8% of viruses including Coronaviruses after 1 hour\*\*

### Sustainable

Resists abrasion and frequent cleaning.

\*Escherichia coli and Staphylococcus aureus, ISO 22196 standard (JIS Z2801) \*\* ISO 21702 standard adapte

# Stamskin quality for healthcare and early childhood environments



Suitable for use in the early childhood sector: fireside chair, motor skills course, mats and tables for changing

# Stamskin <sup>Zen</sup>



F4351-10120



F4351-10120



F4351-20162



F4351-20150



F4351-5015



F4351-20161







F4351-00002



F4351-20293







F4351-20159



F4351-20127





F4351-07459



F4351-07436







F4351-20149









F4351-5349



\* contains no nanoparticles



## 99,9% of bacteria destroyed

24h test protocol (ISO 22196-JIS Z2801)

Non-cytotoxic, does not irritate the skin ISO 10993-5 and -10 standards; OECD TG439





Ease of maintenance due to the smooth grain on the surface

Download the list of compatible detergents and disinfectants





Non-cytotoxic and non-irritant, to respect users' skin



Wellbeing moments with total peace of mind thanks to the Agivir<sup>™</sup> treatment

## Virucidal activity™

## Stamskin Zen

	Technical properties	Standards
Composition	Composite multilayer	
Specific formulation	Phthalates level < 0.1 %	
Backing	Polyamid-jersey	
Weight	780 g/m² ● 23 oz/sq.yd	EN ISO 2286-2
Width	140 cm ● 51.1 in.	
Standard roll length	20 lm • 27.87 yd	
Thickness	0.9 - 1.1 mm • 900 microns - 1,100 microns	EN ISO 5084
	Physical properties	
Elongation under load of 125 N/5 cm (warp/weft)	>35%/>55%	EN ISO 1421
Breaking strength (warp/weft)	> 440 N/5 cm / $>$ 280 N/5 cm	EN ISO 1421
Tear resistance (warp/weft)	>25N/>15N	EN ISO 13937/1
Abrasion resistance	> 120,000 cycles	EN ISO 12947-2
Resistance to bending (no damage)	400 cycles	EN ISO 7854
Cytotoxicity - Extraction method	Compliant	ISO 10993-5
Skin irritation	No reaction - Non irritant	ISO 10993-10 OECDTG439
Antibacterial activity	> 99%	ISO 22196 (JIS Z2801)
Agivir™ Antiviral Surface Treatment	> 99% after 1 hour	ISO 21702 adapted
Extreme operating temperatures	-20°C/+70°C ● -4°F/158°F	
	Fire resistance	
France	M2 Compliant	NFP 92-507
Cigarette test / Match	Noignition	NF EN 1021.1 - 1021.2
Germany	Class F1	DIN 53438-3
Switzerland	VKF 5.3	SN 198898
Italy	Class 2	UNI 9175
United States	Pass Pass	CALTB 117-2013 NFPA 260
Australia	Pass	AS / NZS 1530-3 - Group2 AS/NZS 3837
Marine test	Pass	IMO-MSC-307(88)(2010FTPCode) Annex1Part8
Aeronautical test	Pass	FAR/JAR 25-853 and 25-855
	Management systems	
Quality		ISO 9001
Environment		ISO 14001
	Certifications, labels, warranty	
Smart Coating Technology	5-year warranty	

<sup>1</sup> "+=0" logo: summarises the Serge Ferrari Group's commitment to CSR, to align economic performance and positive impact. Find out about our concrete actions in our CSR report.

The technical characteristics provided are average values with a tolerance of +/- 5%. Our products are subject to change to keep pace with technical advancement and we reserve the right to modify their characteristics at any time. Purchasers of our products must verify that the characteristics shown above are suitable for their purposes. To make a claim under the terms of the warranty, consult the terms of the warranty in question, available upon request.

The transfer of coloring agents such as those contained in pens, clothes or accessories (jeans, dark clothes) are not covered by the warranty. **Upkeep instructions:** simply use a brush and soapy water, to be followed by rinsing with clean water. Avoid the use of stain removers containing solvents or oily products. We recommend the use of Serge Ferrari Cleaner 500. **Implementation**: all usual furniture manufacturing processes involving sewing, stapling, gluing, nailing, etc. Do not use glues containing solvents.

